



Setup Guide for Display Wide Format Prints

Platforms Supported:

Macintosh and Windows 98

Software Supported:

All major Mac/PC software programs, including current versions of QuarkXpress, Pagemaker, Illustrator, Freehand, Photoshop Powerpoint, InDesign, MS Publisher and CorelDraw.

The Best File Format:

TIF, and EPS, file formats are best.

Please Provide Current Prints With Your Files:

Jet Displays requires order form JD4-WF (downloadable) detailing the full specifications of the job, including; type and weight of stock; quantity; how it should be finished; and when it is needed. Having this information from the start helps us to meet the very tight deadlines required for digital print.

Fonts:

Both Mac & PC fonts are supported. *Please Include all fonts including Postscript type 1 (screen and printer fonts) and or Truetype fonts used in your file. (Also include fonts used in all placed graphics.)*

Font Issues:

Avoid using menu style fonts, i.e. bolding, italicizing, underlining, etc. in the style menu. This can cause unexpected results.

Placed Graphics:

All placed Images should be in CMYK mode and should be saved as TIFF or EPS files. (Do not use DCS format or save images with screen angles or transfer functions applied.)

Scanned Images:

Scanned images should be at 150 dpi at 100% scale. Resolution 1200 dpi.

Color Issues:

The RIP automatically converts spot and PMS colors to 4-color CMYK tints. *To avoid unexpected results, work entirely in CMYK mode.* Should you need to get a PMS Match, ask for our Pantone® chart. You will then have to match colors by comparison, and switch to the "best" match on the chart. *Some PMS colors will not convert well.*

Proofs:

We can print proofs at actual size, reduced or a sectional. This will result in an additional charge.

Uploading Files:

Create a folder and place archive file inside the folder. (We recommend you always do this with any uploaded file to ensure all files are kept together and are not "lost" on your hard disk.

Paper Stock:

Paper stock can vary from 35lb heavy coated matte, photogloss, photomatte, wallpaper, vinyl banners, canvas polycarbonate and polyester cloth. We can also print on a number of different stocks such as pressure sensitive labels stock, transparencies and backlit material.

Inks:

Jet Displays offers a choice of brilliant dye based inks, and the longer lasting archival UV pigment based inks.

Turnaround:

Normal turnaround is 48 to 72 hours. Rush service is available at 100% upcharge.

Finishing:

Jet Displays provides basic finishing services including trimming, mounting & laminating, life size cut-outs, velcro and magnetic tape application, grommets and rope. Some finishing processes require additional time to complete. We carry a full line of laminating materials from matte, glossy, lustre (semi-gloss), for both thermal and cold mount applications. Our inventory of mounting boards includes, foam-board, gator-board, komatex (plastic) and posterboard. Our current printer's maximum paper width is 36" wide with a **maximum image area of 34.5"x 150 feet.**
